RCCN 日成LDPE波纹管 Polyethylene Corrugated Tubing

Ral9005

Ral7037

材　质:LDPE 聚乙烯 (Polyethylene)
温　度:-30℃-100℃,短时110℃
结　构:内部和外表均为波浪型。
颜　色:黑色RAL9005,深灰色RAL7037 其它颜色可选购有起订量要求.
产品认证: 欧洲CE, 欧洲环保ROHS, REACH.
特　性:表面好的光泽；柔软；
用　途:可保护电线电缆不受外力磨损及绝缘承载能力:不容易变形，但可以迅速恢复，并且 本身无任何损伤。
应用场合:机器机柜、机床制造、电力设备、自动化装置、食品，包装等机械；
使用方法:将电线电缆穿入管内，再配合日成系列软管接头使用即可.
备　注:带*号为常规备货型号。特殊包装长度有起订量要求,测试温度以日成高低温机测试合格为准，使用需根据现场环境为准。

Material:LDPE (Polyethylene)
Work Temperature:-30℃ to100℃,110℃ in short time
Color:black/ral9005,gray/ral7037
Certificates: CE,ROHS,REACH.
Characheristics:good luster of exterior, stronger machinism loading, perfect flexible
Functions:insulated,protect cables and wires Loading ability:uneasy to change shape,reshape speedly without hurt body
Where to use:Equipment,machines, electricity sets, and so on
How to use:insert cables or wires to RCCN flexible conduit
Remarks:the items with * are available in stock.special packing length come with MOQ work temperature tested according to RCCN factory test machines

单位/Unit:mm

型号 Item No.		规格	内径 I.D.	外径 O.D.	静态弯曲半径	动态弯曲半径	包装 Packing
黑色 Black Ral9005	深灰色 Gray Ral7037	Sizes	A	B	Stat.r	Dyn.r	M
BG-07B/LDPE	BG-07G//LDPE	1/4"	6.5	10.0	15	35	100M
BG-10B/LDPE	BG-10G/LDPE	5/16"	10.0	13.0	20	45	100M
BG-12B/LDPE	BG-12G/LDPE	-	12.0	15.8	25	55	100M
BG-15B/LDPE	BG-15G/LDPE	3/8"	14.3	18.5	35	65	100M
BG-17B/LDPE	BG-17G/LDPE	1/2"	17.0	21.2	40	75	100M
BG-23B/LDPE	BG-23G/LDPE	3/4"	23.0	28.5	45	100	50M
BG-29B/LDPE	BG-29G/LDPE	1"	29.0	34.5	55	120	50M
BG-36B/LDPE	BG-36G/LDPE	1 1/4"	36.0	42.5	65	150	50M
BG-48B/LDPE	BG-48G/LDPE	2"	48.0	54.5	80	190	25M
BG-08B/LDPE	BG-08G/LDPE	9/32"	8.0	11.5	13	25	100M
BG-11B/LDPE	BG-11G/LDPE	-	11.0	14.0	20	45	100M
BG-16B/LDPE	BG-16G/LDPE	-	14.5	20.0	25	55	100M
BG-20B/LDPE	BG-20G/LDPE	-	20.0	25.0	50	85	50M
BG-25B/LDPE	BG-25G/LDPE	-	25.5	31.5	50	110	50M

RCCN 日成LDPEV0阻燃波纹管 Polyethylene Corrugated Tubing



材　质:LDPE 聚乙烯 (Polyethylene)
温　度:-30℃-100℃,短时110℃
结　构:内部和外表均为波浪型。
颜　色:黑色RAL9005,深灰色RAL7037
产品认证: 欧洲CE,ROHS.
防火等级:94-V0。
特　性:表面好的光泽；柔软；
用　途:可保护电线电缆不受外力磨损及绝缘
承载能力:不容易变形，但可以迅速恢复，并且本身无任何损伤。
应用场合:机器机柜、机床制造、电力设备、自动化装置、食品，包装等机械；
使用方法:将电线电缆穿入管内，再配合日成系列软管接头使用即可.
备　注:特殊包装长度有起订量要求,测试温度以日成高低温机测试合格为准，使用需根据现场环境为准。另备环保型阻燃管,有起订量要求。

Material:LDPE (Polyethylene)
Work Temperature:-30℃ to100℃, 110℃ in short time
Color:Color:black/ral9005,gray/ral7037
Certificates: CE,ROHS
Inflaming retarding rate:V-0
Characheristics:good luster of exterior, stronger machinism loading, perfect flexible
Functions:insulated,protect cables and wires
Loading ability:uneasy to change shape,reshape speedly without hurt body
Where to use:Equipment,machines, electricity sets, and so on.
How to use:insert cables or wires to RCCN flexible conduit
Remarks:the items with * are available in stock. special packing length come with MOQ work temperature tested according to RCCN factory test machines

单位/Unit:mm