





Product Service

**Attestation of Conformity**  
**No. N8A 15 09 93168 002**

**Model(s):**

MG12A-08, MG16A-07, MG16A-10, MG20A-11, MG20A-14,  
 MG25A-16, MG25A-18, MG32A-22, MG32A-25, MG40A-25,  
 MG40A-30, MG50A-32, MG50A-40, MG63A-46, MG63A-50,  
 PG7A-08, PG9A-05, PG9A-08, PG11A-07, PG11A-10,  
 PG13.5A-08, PG13.5A-12, PG16A-11, PG16A-14, PG21A-16,  
 PG21A-18, PG29A-22, PG29A-25, PG36A-25, PG36A-30,  
 PG42A-32, PG42A-40, MGB12S-06B, MGB12-07B, MGB12L-07B,  
 MGB16S-08B, MGB16SL-08B, MGB16-10B, MGB16L-10B, MGB18-10B,  
 MGB18L-10B, MGB20S-12B, MGB20-14B, MGB20L-14B, MGB25S-14B,  
 MGB25-18B, MGB25L-18B, MGB32-22B, MGB32-25B, MGB40-32B,  
 MGB50-40B, MGB63-46B, PGB7-07, PGB9-08, PGB13.5-12,  
 PGB16 -14, PGB19 -14, PGB21-18, PGB25-20, PGB29-25,  
 PGB36-32, PGB42-41, PGB48-46

**Parameters:**

Material of the cable glands:	Non-metallic
Type of cable anchorage:	Anchorage Type A
Impact category:	Category 1
Degree of protection:	IP54
Temperature range:	-40°C to 85 °C
Sealing system:	With a single orifice seal

**Tested according to:**

EN 62444:2013